

416 Rec'd PCT/PTO 07 JUN 2000

AMENDED CLAIMS

1. A method of calculating the fast Fourier transform or the inverse fast Fourier transform of a digital signal defined by a series of N real starting
- 5 samples $x(n)$, with N a power of two and $n \in [0..N-1]$, comprising successive transformation steps (2) for transforming input samples into output samples, (all the transformation steps being performed by means of a
- 10 single set of butterflies with several inputs and several outputs, the operating mode of which is modified selectively in each transformation step, the input and output samples of each transformation step being stored in a storage memory, a series of N output
- 15 samples $y(n)$ representative of the fast Fourier transform or the inverse fast Fourier transform of the output samples $x(n)$ being provided in the last transformation step,
- characterized in that output samples $y(n)$ are real,
- 20 and in that the output samples of a butterfly replace the corresponding input samples of the same rank in the storage memory, so that, if the starting samples $x(n)$ processed in the first transformation step are classified in bit-reversed order of their index n,
- 25 output samples $y(n)$ are provided in the last transformation step in ascending order of index n, these output samples being defined by the following relations:

$$y(0) = \text{Re}[X(0)]$$

$y(n) = \text{Re}[X((n+1)/2)]$ for n being odd and
different from $N-1$

$y(n) = \text{Im}[X(n/2)]$ for n being even and
different from 0

5 $y(N-1) = \text{Re}[X(N/2)]$

where samples $X(n)$, with $n \in [0..N-1]$, designate the complex samples of the series corresponding to the fast or inverse fast Fourier transform of the starting sample series $x(n)$.

10 2. A method of calculating the fast Fourier transform or the inverse fast Fourier transform of a digital signal defined by a series of N complex samples $X(n)$ conjugated by pairs, characterized in that the calculation is done on a series of N real starting samples $y(n)$ representative of the series of complex samples $X(n)$, with N power of two and $n \in [0..N-1]$, the starting samples $y(n)$ being defined as follows:

$y(0) = \text{Re}[X(0)]$

$y(n) = \text{Re}[X((n+1)/2)]$ for n being odd and
different from $N-1$

$y(n) = \text{Im}[X(n/2)]$ for n being even and
different from 0

$y(N-1) = \text{Re}[X(N/2)]$

in that this method comprises successive transformation steps for transforming input samples into output samples, a series of N real output samples $x(n)$ representative of this fast or inverse fast Fourier transform being provided in the last transformation step, all the transformation steps being performed by means of a single set of butterflies with several inputs and several outputs, the operating mode of which

is modified selectively in each transformation step, the input and output samples of each transformation step being stored in a storage memory,

and in that the output samples of a butterfly
5 replace the corresponding input samples of the same rank in the storage memory, so that, if the starting samples $y(n)$ processed in the first transformation step are classified in ascending order of index n , the output samples $x(n)$ are provided in the last
10 transformation step in bit-reversed order of index n .

3. The calculation method according to claim 1 or
2, characterized in that, in each transformation step, each butterfly transforms input sample pairs, the ranks of the input samples of the same pair within the series
15 of input samples of said transformation step being symmetrical with respect to a center between the end rank values of the input samples transformed by said butterfly.

4. The calculation method according to claim 3,
20 characterized in that it comprises $\mu-1$ transformation steps E_p with $\mu = \log_2(N)$ and $p \in [0.. \mu-2]$.

5. The calculation method according to claim 4, (in
turn dependent on claim 3, in turn dependent on claim
25 1,) characterized in further comprising:

- a preliminary step of modifying the sequence of the starting samples $x(n)$ ranked in ascending order of index n and showing them in bit-reversed order of index n in the first transformation step, and
- 30 - a final step of processing the series of output samples $y(n)$ and providing a series of N complex

Function
24
36
48
60
72
84
96
108
120
132
144
156
168
180
192
204
216
228
240
252
264
276
288
300
312
324
336
348
360
372
384
396
408
420
432
444
456
468
480
492
504
516
528
540
552
564
576
588
600
612
624
636
648
660
672
684
696
708
720
732
744
756
768
780
792
804
816
828
840
852
864
876
888
900
912
924
936
948
960
972
984
996

al

conjugated samples $X(n)$ corresponding to the fast or the inverse fast Fourier transform of the series of starting samples $x(n)$.

6. The calculation method of claim 4, (in turn dependent on claim 3, in turn dependent on claim 1, or according to claim 5,) characterized in that, in each transformation step E_p , butterflies are distributed among $N/2^{p+2}$ calculation blocks,

in that each calculation block has a peripheral butterfly and/or 2^p-1 internal butterflies,

in that the peripheral butterfly of the rank α calculation block in transformation step E_p transforms the input samples of rank $2^{\beta+2}\alpha$, $2^{\beta+2}\alpha+2^{\beta+1}-1$, $2^{\beta+2}\alpha+2^{\beta+1}$, $2^{\beta+2}\alpha+2^{\beta+2}-1$ into output samples of the same rank,

and in that the internal rank τ butterfly of the rank α calculation block in transformation step E_p transforms the input samples of rank $2^{\beta+2}\alpha+2\tau+1$, $2^{\beta+2}\alpha+2\tau+2$, $2^{\beta+2}\alpha+2^{\beta+2}-2\tau-3$, $2^{\beta+2}\alpha+2^{\beta+2}-2\tau-2$ into output samples of the same rank, with $\beta \geq 1$.

7. The calculation method according to claim 6, characterized in that each butterfly is assigned a coefficient W^s , whereon the calculation inside the butterfly is based, said coefficient being equal to $e^{-j(2\pi s/N)}$ with $s \in [0..N/4-1]$ for a fast Fourier transform and is equal to $e^{j(2\pi s/N)}$ with $s \in [0..N/4-1]$ for an inverse fast Fourier transform.

8. Calculation method according to claim 7, characterized in that the internal rank τ butterfly of the rank α calculation block in transformation step E_p is assigned coefficient W^δ with $\delta = (\tau+1) \cdot (N/2^{\beta+2})$.

9. The calculation method according to claim 8, characterized in that the butterflies for implementing the transformation steps are all of the same type and have

- 5 - four inputs for receiving input samples and four outputs for providing output samples,
 - four additional inputs, respectively primary mode, secondary mode, permutation, and coefficient inputs,

10 in order to selectively apply different transformation operations to the input samples, each operation being determined by the values assigned to the primary mode, secondary mode, permutation signals, and a coefficient admitted on said corresponding
15 additional inputs.

al 10. The calculation method according to claim 9, characterized in that, for each butterfly, the primary mode signal is 0 for a peripheral butterfly and 1 for an internal butterfly,

20 in that the permutation signal is 0 for the even rank calculation blocks, including rank 0, and 1 for the other ones.

 11. The calculation method according to claim 10, characterized in that, in transformation step E_p , each
25 calculation block comprises one peripheral butterfly and $2^p - 1$ internal butterflies.

 12. The calculation method according to claim 11, characterized in that the secondary mode signal is 1 if the peripheral butterfly is used for the last
30 transformation step, and otherwise 0.

13. The calculation method according to claim 12, characterized in that, for four input samples e_1 , e_2 , e_3 , and e_4 , and for a complex coefficient $W^S=A+j.B$, the butterfly delivers the following output samples s_1 , s_2 , s_3 , and s_4

1) if the primary mode and secondary mode signals are 0: $s_1 = e_1 + e_2$

$$s_2 = e_1 - e_2$$

$$s_3 = e_4 - e_3$$

10 $s_4 = e_3 + e_4$

2) if the primary mode signal is 0 and the secondary mode signal is 1:

$$s_1 = e_1 + e_2 + e_3 + e_4$$

$$s_2 = e_1 - e_2$$

15 $s_3 = e_4 - e_3$

$$s_4 = (e_1 + e_2) - (e_3 + e_4)$$

3) if the primary mode signal is 1 and the permutation signal is 0:

$$s_1 = e_1 + A.e_3 - B.e_4$$

20 $s_2 = e_2 + B.e_3 + A.e_4$

$$s_3 = e_1 - A.e_3 + B.e_4$$

$$s_4 = -e_2 + B.e_3 + A.e_4$$

4) if the primary mode signal is 1 and the permutation signal is 1:

25 $s_1 = e_1 - A.e_3 + B.e_4$

$$s_2 = -e_2 + B.e_3 + A.e_4$$

$$s_3 = e_1 - A.e_3 - B.e_4$$

$$s_4 = e_2 + B.e_3 + A.e_4$$

14. The calculation method according to claim 10, characterized in that, in transformation step E_p , each calculation block comprises:

- 2^p-1 internal butterflies and a peripheral butterfly for the even values of index p as well as for the last transformation step if p is even, and

- 2^p-1 internal butterflies, otherwise.

5 15. The calculation method according to claim 13, characterized in that the secondary mode signal is 1 if the peripheral butterfly is used for the last transformation step with p being odd, and otherwise 0.

10 16. The calculation method according to claim 15, characterized in that, for four input samples e_1 , e_2 , e_3 , and e_4 , and for a complex coefficient $W^s=A+j.B$, the butterfly delivers the following output samples s_1 , s_2 , s_3 , and s_4

15 1) if primary mode, secondary mode and permutation signals are 0:

$$s_1 = e_1 + e_2 + e_3 + e_4$$

$$s_2 = e_1 - e_2$$

$$s_3 = e_4 - e_3$$

$$s_4 = (e_1 + e_2) - (e_3 + e_4)$$

20 2) if the primary mode signal is 0 and the secondary mode signal is 1:

$$s_1 = e_1 + e_4$$

$$s_2 = e_2$$

$$s_3 = e_3$$

25 $s_4 = e_1 - e_4$

3) if the primary mode signal is 0 and the permutation signal is 1:

$$s_1 = (e_3 + e_4) - (e_1 + e_2)$$

$$s_2 = e_1 - e_2$$

30 $s_3 = e_4 - e_3$

$$s_4 = e_1 + e_2 + e_3 + e_4$$

4) if the primary mode signal is 1 and the permutation signal is 0:

$$s1 = e1 + A.e3 - B.e4$$

$$s2 = e2 + B.e3 + A.e4$$

5 $s3 = e1 - A.e3 + B.e4$

$$s4 = -e2 + B.e3 + A.e4$$

5) if the primary mode signal is 1 and the permutation signal is 1:

$$s1 = e1 - A.e3 + B.e4$$

10 $s2 = -e2 + B.e3 + A.e4$

$$s3 = e1 + A.e3 - B.e4$$

$$s4 = e2 + B.e3 + A.e4$$

17. The calculation method according to claim 10, characterized in that, in transformation step E_p , each calculation block comprises:

- a1
- 2^p-1 internal butterflies and a peripheral butterfly for the even values of index p , and
 - 2^p-1 internal butterflies, otherwise.

18. The calculation method according to claim 17, characterized in that the secondary mode signal is 1 if the peripheral butterfly is used for the first transformation step with μ being even, and otherwise 0.

19. The calculation method according to claim 18, characterized in that, for four input samples $e1$, $e2$, $e3$, and $e4$, and for a complex coefficient $W^S=A+j.B$, the butterfly delivers the following output samples $s1$, $s2$, $s3$, and $s4$

1) if the primary mode signal is 0 and the secondary mode signal is 1:

30 $s1 = e1 + e2$

$$s2 = e1 - e2$$

$$s3 = e4 - e3$$

$$s4 = e3 + e4$$

2) if primary mode, secondary mode and permutation signals are 0:

$$5 \quad s1 = e1 + e2 + e3 + e4$$

$$s2 = e1 - e2$$

$$s3 = e4 - e3$$

$$s4 = (e1 + e2) - (e3 + e4)$$

3) if the primary mode and secondary mode signals
10 are 0 and the permutation signal is 1:

$$s1 = (e3 + e4) - (e1 + e2)$$

$$s2 = e1 - e2$$

$$s3 = e4 - e3$$

$$s4 = e1 + e2 + e3 + e4$$

15 *a1* 4) if the primary mode signal is 1 and the permutation signal is 0:

$$s1 = e1 + A.e3 - B.e4$$

$$s2 = e2 + B.e3 + A.e4$$

$$s3 = e1 - A.e3 + B.e4$$

$$20 \quad s4 = -e2 + B.e3 + A.e4$$

5) if the primary mode signal is 1 and the permutation signal is 1:

$$s1 = e1 - A.e3 + B.e4$$

$$s2 = -e2 + B.e3 + A.e4$$

$$25 \quad s3 = e1 + A.e3 - B.e4$$

$$s4 = e2 + B.e3 + A.e4$$

20. The calculation method according to claim 8, characterized in that the butterflies for implementing the transformation steps are all of the same type and
30 have

- four inputs for receiving input samples and four outputs for providing output samples,

- four additional inputs, respectively primary mode, secondary mode, permutation, and coefficient
5 inputs,

in order to selectively apply different transformation operations to the input samples, each operation being determined by the values assigned to the primary mode, secondary mode, permutation signals,
10 and a coefficient admitted on said corresponding additional inputs,

and in that the final step furthermore performs an addition and subtraction between the first and the last output sample provided in the last transformation step.

21. The calculation method according to claim 20,
15 characterized in that, in transformation step E_p , each calculation block comprises one peripheral butterfly and 2^p-1 internal butterflies.

22. The calculation method according to claim 21,
20 characterized in that, for four input samples e_1 , e_2 , e_3 , and e_4 , and for a complex coefficient $W^s = A + j.B$, the butterfly delivers the following output samples s_1 , s_2 , s_3 , and s_4

1) if the primary mode signal is 0:

25 $s_1 = e_1 + e_2$
 $s_2 = e_1 - e_2$
 $s_3 = e_4 - e_3$
 $s_4 = e_3 + e_4$

2) if the primary mode signal is 1 and the
30 permutation signal is 0:

$s_1 = e_1 + A.e_3 - B.e_4$

$$s2 = e2 + B.e3 + A.e4$$

$$s3 = e1 - A.e3 + B.e4$$

$$s4 = -e2 + B.e3 + A.e4$$

3) if the primary signal is 1 and the permutation
5 signal is 1:

$$s1 = e1 - A.e3 + B.e4$$

$$s2 = -e2 + B.e3 + A.e4$$

$$s3 = e1 + A.e3 - B.e4$$

$$s4 = e2 + B.e3 + A.e4$$

10 23. The calculation method according to claim 9 or
20, characterized in that the first and second binary
addresses of μ bits are generated for each butterfly,
each binary address corresponding to the rank of an
input sample of said butterfly and the second binary
15 address being greater than the first binary address.

a1 24. The calculation method according to claim 23,
characterized in that said first and second binary
addresses are consecutive and an internal butterfly is
involved.

20 25. The calculation method according to claim 23
or ~~24~~, characterized in that, if a peripheral butterfly
is involved, the $p+2$ low-order bits of the first
address are equal to 0, and the $p+2$ low-order bits of
the second address form a number equal to $2^{p+1}-1$.

25 26. The calculation method according to claim 24
or ~~25~~, characterized in that the address of the two
other samples to be applied to the inputs of the
butterfly, be they peripheral or internal, are obtained
by inverting the $(p+2)$ low-order bits of said first and
30 second produced addresses.

27. The calculation method according to claim 26, characterized in that even-numbered address samples and odd-numbered address samples are stored in two separate memories.

5 28. The calculation method according to claim 25, characterized in that the value of the parameter s of the coefficient W^s assigned to an internal butterfly in transformation step E_p is coded by $\mu-2$ bits, and is:

10 - if $p+1=\mu-2$, the number formed by the $p+1$ low-order bits of the second binary address produced for said internal butterfly,

15 - if $p+1<\mu-2$, the number formed by the $p+1$ low-order bits of the second binary address produced for said internal butterfly, followed by $\mu-p-3$ zero bits at the end of the number,

a1 - if $p+1>\mu-2$, the number formed by the $p+1$ low-order bits of the second binary address produced for said internal butterfly, minus its $\mu-p-1$ low-order bits.

20 29. The calculation method according to claim 4, (in turn dependent on claim 3, in turn dependent on claim 2,) characterized in that in each transformation step E_p , the butterflies are distributed among 2^p calculation blocks,

25 in that each calculation block comprises one peripheral butterfly and $N/2^{p+2}-1$ internal butterflies,

30 in that the peripheral butterfly of the rank α calculation block in transformation step E_p transforms the input samples of rank $2^{\mu-\beta}\alpha$, $2^{\mu-\beta}\alpha+2^{\mu-\beta-1}-1$, $2^{\mu-\beta}\alpha+2^{\mu-\beta}-1$, $2^{\mu-\beta}\alpha+2^{\mu-\beta}-1$ into output samples of the same rank,

and in that the internal rank τ butterfly of the rank α calculation block in transformation step E_β transforms the input samples of rank $2^{\mu-\beta}\alpha+2\tau+1$, $2^{\mu-\beta}\alpha+2\tau+2$, $2^{\mu-\beta}\alpha+2^{\mu-\beta-1}-2\tau-3$, $2^{\mu-\beta}\alpha+2^{\mu-\beta}-2\tau-2$ into output
 5 samples of the same rank.

30. The calculation method according to claim 29, characterized in further comprising a final step of modifying the sequence of the output samples provided in the last transformation step and classifying them in
 10 ascending order of index n .

31. The calculation method according to claim 29 or ~~30~~, characterized in that each butterfly is assigned a coefficient W^s , whereon the calculation inside the butterfly is based, said coefficient being equal to $e^{-j(2\pi s/N)}$
 15 $j(2\pi s/N)$ with $s \in [0..N/4-1]$ for a fast Fourier transform and is equal to $e^{j(2\pi s/N)}$ with $s \in [0..N/4-1]$ for an inverse fast Fourier transform.

32. Calculation method according to claim 31, characterized in that the internal rank τ butterfly of
 20 the rank α calculation block in transformation step E_β is assigned coefficient W^δ with $\delta = (\tau+1).2^\beta$.

33. The calculation method according to claim 32, characterized in that the butterflies for implementing the transformation steps are all of the same type and
 25 have

- four inputs for receiving input samples and four outputs for providing output samples,
- four additional inputs, respectively primary mode, secondary mode, permutation, and coefficient
 30 inputs,

in order to selectively apply different transformation operations to the input samples, each operation being determined by the values assigned to the primary mode, secondary mode, permutation signals, and a coefficient admitted on said corresponding additional inputs.

34. The calculation method according to claim 33, characterized in that, for each butterfly, the primary mode signal is 0 for a peripheral butterfly and 1 for an internal butterfly,

in that the permutation signal is 0 for the even rank calculation blocks, including rank 0, and 1 for the odd values.

35. The calculation method according to claim 31 or ~~34~~, characterized in that the secondary mode signal is 1 if the butterfly, be it peripheral or internal, is used for the first transformation step, and otherwise 0.

36. The calculation method according to claim 35, characterized in that, for four input samples e_1 , e_2 , e_3 , and e_4 , and for a complex coefficient $W^S = A + j.B$, the butterfly delivers the following output samples s_1 , s_2 , s_3 , and s_4

1) if the primary mode and secondary mode signals are 0:

$$s_1 = (e_1 + e_2)/2$$

$$s_2 = (e_1 - e_2)/2$$

$$s_3 = (e_4 - e_3)/2$$

$$s_4 = (e_3 + e_4)/2$$

2) if the primary mode signal is 0 and the secondary mode signal is 1:

$$s1 = [(e1+e4)/2-e2]/2$$

$$s2 = [(e1+e4)/2-e2]/2$$

$$s3 = [e3-(e1-e4)/2]/2$$

$$s4 = [e3+(e1+e4)/2]/2$$

5 3) if the primary mode signal is 1 and the permutation signal is 0:

$$s1 = (e1+e3)/2$$

$$s2 = (e2+e4)/2$$

$$s3 = [(e1-e3).A - (e2+e4).B]/2$$

10 $s4 = [-(e1-e3).B + (e2+e4).A]/2$

4) if the primary mode signal is 1 and the permutation signal is 1:

$$s1 = [(e1-e3).A - (e2+e4).B]/2$$

$$s2 = [-(e1-e3).B + (e2+e4).A]/2$$

15 $s3 = (e1+e3)/2$

$$s4 = (e2-e4)/2$$

al 37. The calculation method according to claim 33, characterized in that the first and second binary addresses of μ bits are generated for each butterfly, each binary address corresponding to the rank of an input sample of said butterfly and the second binary address being greater than the first binary address.

20 38. The calculation method according to claim 37, characterized in that said first and second binary addresses are consecutive and an internal butterfly is involved.

30 39. The calculation method according to claim 37 or 38, characterized in that, if a peripheral butterfly is involved, the μ -p low-order bits of the first address are equal to 0, and the μ -p low-order bits of the second address form a number equal to $N/2^{p+1}-1$.

40. The calculation method according to claim 38 or ~~39~~, characterized in that the address of the two other samples to be applied to the inputs of the butterfly are obtained by inverting the μ -p low-order bits of both produced addresses.

41. The calculation method according to claim 40, characterized in that even-numbered address samples and odd-numbered address samples are stored in two separate memories.

42. The calculation method according to claim 41, characterized in that the value of the parameter s of the coefficient W^s assigned to an internal butterfly in transformation step E_p is coded by μ -2 bits, and is:

a - if μ -p-1= μ -2, the number formed by the μ -p-1 low-order bits of the second address produced for said internal butterfly,

- if μ -p-1< μ -2, the number formed by the μ -p-1 low-order bits of the second address produced for said internal butterfly, followed by p-1 zero bits at the end of the number,

- if μ -p-1> μ -2, the number formed by the μ -p-1 low-order bits of the second address produced for said internal butterfly, minus its p+1 low-order bits.
